



ZEBRA MK3100 MICRO KIOSK

AFFORDABLE ALL-IN-ONE MULTIMEDIA MICRO KIOSK FOR RETAIL, HOSPITALITY AND MORE

TAKE SELF-SERVICE TO A NEW LEVEL WITH RICH AND INTUITIVE INTERACTIVE OPTIONS Today's shoppers, guests and travelers want to choose how to get the service they need — from a person or from a self-service kiosk. And with over 90 percent¹ reporting the use of self-service kiosks, providing self service devices is crucial to meeting those service expectations — and the success of your organization. With the MK3100 Micro Kiosk, you'll have all the features you need to deliver an impressive self-service experience. This powerful device supports simple applications such as price and inventory checks to highly intuitive and elegantly designed multimedia applications such as how-to or product informational videos and product catalogs, allowing shoppers, guests and travelers to get the information they need quickly and easily. Deliver self-service with a difference — with the MK3100.

Best-in-class processing power

A 1GHz processor, 1GB RAM/8GB Flash and up to 32GB of additional memory via the MicroSD card slot provides power for the most complex multimedia applications — and the most powerful platform in its class.

Full screen video support

Enables the delivery of rich video-based information to better engage with customers and employees. How-to and product demonstration videos provide added value for customers. Training videos help improve sales skills and keep employees up to date on new items. And the ability to run video advertisements when the device is not in use helps you get more out of your advertising budget — and the MK3100.

Easy to deploy

802.11a/b/g/n and Ethernet support enables easy connection to your existing wireless or wired network; 'n' support provides the bandwidth for data intensive multimedia apps; 'a' can be used for critical store wireless infrastructure only to preserve performance; Power-over-Ethernet support eliminates the need for a power outlet by every device; and standard VESA mounting makes it easy to mount anywhere — including shelves, walls and endcaps.

Capture any bar code

Scan 1-D and 2-D bar codes printed on paper labels, plastic loyalty or gift cards or displayed on the screen of a mobile phone.

Add whatever you need — from memory to peripherals.

Three user-accessible USB ports plus Bluetooth allow you to customize the MK3100 to meet your business needs. Add memory for demanding applications. Add a wireless or wired printer to allow customers to print receipts, gift registries and more; a magnetic stripe reader to allow self-checkout; and a keyboard to simplify data entry.

Use mobile bar codes to build stronger and more personal relationships with your customers

WHAT CAN THE MK3100 DO FOR YOUR BUSINESS?

Retail

- Price check
- Inventory check
- Informational product videos
- How-to videos for customers
- Training videos for employees
- Gift card purchase/lookup
- Gift registry creation and lookup
- Digital advertising/signage
- Loyalty points lookup/coupons
- In-store pickup of web-based orders/li>
- Mobile bar code support/mobile coupons
- Large ticket item sales support
- Coupon printing
- Call for assistance
- Guided selling
- Merchandise locator
- CD preview/li>
- Store maps

WorkForce Management

- Time clock
- Work schedules
- Task management

Healthcare

- Patient self check-in
- Patient portal
- Procedure information
- Medication administration
- Patient administration

Hospitality

- Hotel room guest portal
- Electronic concierge
- Hotel maps

Since you can scan electronic bar codes on a computer screen, you can connect to the one personal device that is nearly always in the hands of your customers—their mobile phone. The result is convenience and value. Customers always have their loyalty cards, coupons, boarding passes and more on hand all the time, saving time and money.

Transportation, Travel and Entertainment

- E-ticket purchase
- E-ticket pick up
- Boarding/self check-in

RhoMobile Suite support for OS-agnostic elegant applications

Write one version of an application that can run on any device with any operating system, maximizing app development investments; true freedom from operating system constraints allows you to design business applications with the most sophisticated and easy to use consumer-style interfaces.

THE MK3100 — COMPLEX SELF SERVICE APPLICATIONS MADE SIMPLE.

For more information, visit www.zebra.com/mk3100 or access our global contact directory at www.zebra.com/contact

TECHNICAL SPECIFICATIONS

PHYSICAL CHARACTERISTICS		COMMUNICATIONS	
Dimensions	8.87 in. H x 8.87 in. L x 2.17 in. W 22.5 cm H x 22.5 cm L x 5.5 cm W	WLAN	802.11a/b/g/n
Weight	1.9 lbs./0.86 kg	WPAN	Bluetooth 2.1 + EDR
Display	8 in./20.32 cm diagonal WVGA LCD; 800 x 480 pixels; resistive touch screen	Ethernet	10/100 Mb Ethernet; supports Power-over-Ethernet 802.3af
Power	DC: 12v; Support for Power-over-Ethernet (802.3af and 802.3at)	PERFORMANCE CHARACTERISTICS	
Expansion Capabilities	User accessible MicroSD card slot; USB host	CPU	TI OMAP4 1GHz processor
Data Ports	1 Mini USB 2.0 host/client; 2 Mini USB 2.0 host; Ethernet RJ-45	Operating System	Windows Embedded Compact 7
Audio	Two integrated stereo speakers, microphone and headset jack	Browser	Internet Explorer 7.0; RhoElements
Scanner	Imager for capture of 1-D, 2-D, and PDF417 codes	Memory	1 GB RAM/8 GB Flash
Keys	Four programmable keys	Additional Memory	Up to 32 GB flash via accessible microSD slot
SYMBOLGY DECODE CAPABILITY		PERIPHERALS AND ACCESSORIES	
2-D Imager Scanner Decode Capability	1-D: Code 39, Code 128, EAN-8, EAN-13, UPCEAN-128, UPCA, UPCE, UPC/EAN Supplementals, GS1 DataBar, Chinese 2 of 5, Code 93, Discrete 2 of 5, Interleaved 2 of 5 (including ITF14 and ITF 2 of 5), Codabar, ISBT 128 2-D: PDF417, QR, Aztec, DataMatrix and MaxiCode	Mounting Options	Conforms to the VESA 100mm mounting standard for attachment of third-party, off-the-shelf mounting solutions; four (4) M4 x 8.1 mm inserts provided
USER ENVIRONMENT		REGULATORY	
		Electrical Safety	UL60950-1/CSA C22.2 No. 60950-1, EN60950-1/IEC60950-1
		EMI/RFI	EN 301 489-1, EN 301 489-17, EN 55022, FCC Part 15 Class B, ICES 003 Class B, EN 55024, EN 61000 -3-2, EN 61000-3-3, AS/NZS 4268: 2008, Japan VCCI
WARRANTY			

Operating Temp.	32° to 104° F / 0° to 40° C
Storage Temp.	-40° to 158° F / -40° to 70° C
Humidity	5% to 85% (non-condensing)
Application Development Tools	RhoMobile Suite for web development; Enterprise Mobility Developer Kit (EMDK) for C for developing native C/C++ applications; Enterprise Mobility Developer Kit (EMDK) for .NET for developing managed .NET applications in C# or VB.NET
Management Tools	Rapid Deployment Client; Zebra Mobility Services Platform (MSP)
Ambient Light Immunity	Immune to normal indoor lighting up to 1600 Lux; immune to sunlight up to 86,000 Lux

Subject to the terms of Zebra's hardware warranty statement, the MK3100 is warranted against defects in workmanship and materials for a period of 1 year from the date of shipment. For the complete Zebra hardware product warranty statement, go to: www.zebra.com/warranty

RECOMMENDED SERVICES

Service from the Start Advance Exchange Support

For Regulatory Approvals:
MK3100 (LAN) and MK3190 (WLAN and Bluetooth)

1 2009 Self-Service Consumer Survey, Network Alliance LLC; © 2009



Part number: PSS-MK3100. Printed in USA 04/15.©2015 ZIH Corp. ZEBRA, the Zebra head graphic and Zebra Technologies logo are trademarks of ZIH Corp, registered in many jurisdictions worldwide. All rights reserved. All other trademarks are the property of their respective owners.

ZEBRA TECHNOLOGIES